



# G1Fi™ System ID™ Optics + LRF

G1Fi™ is a product culminating several years of development. It offers the best capabilities of G and T series product:

- State-of-the-art optical riflescope with anti-reflective low light performance coatings
- Second focal plane reticle maintaining the same appearance throughout the 1-8x zoom range
- Glass-etched illuminated reticle with brightness control for low light conditions
- USB port with power input and software updates
- CR123 or rechargeable battery
- 1000 meter LRF module with full controls
- First system to use ID™ embedded display technology

G1™	
<b>Magnification</b>	1-8x
<b>Objective Lens Diameter</b>	24 mm
<b>Exit Pupil</b>	24-3 mm
<b>Eye Relief</b>	35 in / 89 mm
<b>Diopter Adjustment</b>	±4
<b>Field-of-View</b>	116.5-14.4 ft / 100 yds
<b>Field-of-View</b>	38.6 - 4.7 m / 100 m
<b>Tube Diameter</b>	30 mm
<b>Turret Style</b>	Capped, Finger Adjusted
<b>Click Value</b>	1/2 MOA
<b>Elevation Adjust. Range</b>	45 MOA
<b>Windage Adjust. Range</b>	45 MOA
<b>Parallax Setting</b>	100 yds
<b>Size (L x W x H)</b>	10x3x3 in / 254x76x76 mm
<b>Weight</b>	23 oz / 652 g
<b>Picatinny Mount Height</b>	1.5 in / 38.1 mm
<b>Illuminated Reticle Battery</b>	CR2032
<b>Internal Display</b>	Monochrome Yellow OLED
<b>Display Interface</b>	Special USB
<b>Environmental</b>	IP67

F1™	
<b>Range</b>	1,500 yds/m
<b>Accuracy</b>	5 to 1,500 yds/m ±1 yd/m
<b>Display</b>	1/2" white OLED
<b>Metric/Imperial</b>	Yes, selected
<b>Laser</b>	905 nm, Eye Safe Class I
<b>Measuring Time</b>	<0.25 sec
<b>Remote Control</b>	Included
<b>Remote Display</b>	Yes, connects to ID™
<b>Size</b>	100 x 30 x 30 mm
<b>Weight</b>	200 g (without battery)
<b>Power</b>	3V CR123 or rechargeable
<b>Environmental</b>	IP67

G1Fi™	
<b>Size (LxWxH)</b>	12.8 x 3.1 x 4.7 in / 325 x 79 x 118 mm
<b>Weight with Mount</b>	34.2 oz / 970 g

ID™ Internal Display is a Registered Trademark of Torrey Pines Logic, Inc. Patents pending for ID, G1 and T series and its components

