



B5™ LRF Binoculars

Accurate Distance Measurement

- “One touch” operation
- OLED easy-to-read display
- Three modes of ranging:
M1 - Linear mode; M2 - Horizontal mode; M3 - Vertical mode
- Super accurate ranging at distances up to 2 km
- Bright optics with 10x magnification
- Large prisms with phase and dielectric coating
- Magnesium body



B5 LRF	10X45	B5 LRF	10X45
Magnification	10x	Relative Brightness	20.25
Objective Lens Diameter	45 mm	Diopter Adjustment	±3dpt
Objective	4E/4G	Interpupillary Distance	56-76 mm
Eyepiece	5E/3G	Weatherproof	Yes
Lens Coating	FMC	Waterproof	1 m/15 min
Focus System	Center	Nitrogen Filled	Yes
Exit Pupil Diameter	4.5 mm	Twist Eyecaps	Yes
Exit Pupil Distant	18 mm	Dimension	157 x 137 x 67 mm
Field-of-View	6.2°	Weight	920 g
F.O.V at ft/1000 yds	326	Body Material	Magnesium
F.O.V at m/1000 m	108	Measuring Range	2000 m
Min. Focal Distance	5 m	Repetitive Rate	≤200 m, ±1 m ; ≥200 m, ±0.5% m
Twilight Index	21.2	Battery Use	CR2

